

CV-IP2PT-4
3Inch 2.0MP WiFi IP speed dome Q Series



Feature :

- 1/2.9" Low-illumination CMOS sensor;
- HD 1080P Resolution, Image clear, Delicate;
- Day/Night(Auto ICR);
- Auto electronic shutter time;
- IR range: 4*White Light ,4*Infrared Light 40m-50m;
- Support wired and wireless (wifi) network connection
- Ingress Protection : IP65 ;
- Support DWDR, 3D DNR;
- H.265AI/H.265+(compatible H.265/H.264) encoding algorithm;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Information superposition (ID, IP, DDNS etc.)
- Support WEB, CMS, VMS, MYEYE, Cloud services;
- Support HVR/NVR, Onvif protocol;
- Support AI functions config like Face detection and human detect etc ;

Scenarios :

Apply for road,warehouse,underground parking lot,bar,pipeline and somewhere where require HD images but with dark light and poor sunshine.

Model :

CV-IP2PT-4

Dimension :

Parameters :

	Model	CV-IP2PT-4
Camera	sensor	1/2.9" Low-illumination CMOS sensor
	Min. illumination	Color : 0.01Lux @(F1.2,AGC ON); 0 Lux with B/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux with
	Shutter time	automatic
	Max.image	1920*1080
	Frame rate	PAL: 1080P@12fps NTSC: 1080P@12fps
	Day&night	IR cut filter with auto switch
	Lens	Aperture
Lens		3.6mm
Function	IR range	4*White Light ,4*Infrared Light "IR4" :40-50m
	Rotation rangeStorage	Horizontal : 0° ~ 320° continuous rotation; Vertical : -10° ~ 90° continuous monitoring
	Intercom	Support
	Cloud storage	Support (free for 30 days)
	protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, (HTTPS, SIP, 802.1x, IPv6 Optional)
	Storage	Network storage ,SD card (up to 128G, self made)
Interface	AudioI/O	1/0+loudspeaker
	AlarmI/O	0/0
	Ethernet	1*10/100Mbps Ethernet port, RJ45 port +WiFi
General	temperature	-20°C~65°C
	humidity	10%-90% RH
	Power supply	DC12V/2A
	Material	ABS plastic
	Ingress Protection	IP65 , TVS4000V Lightning-Proof and Anti-Surge
	Weight	Around 500g
Dimension	180*110*170mm	